การลดการปนเปื้อนของ Escherichia coli และแบคทีเรีย Coliform ในหน่อไม้ฝรั่งเพื่อการส่งออก

พนิดา ภควันต์*

บทคัดย่อ

การศึกษาการปนเปื้อนของแบคทีเรีย Escherichia coli และ Coliform ในกระบวนการผลิตหน่อ ไม้ฝรั่งเพื่อการ ส่งออก ตั้งแต่แปลงปลูกของเกษตรกร จุดผู้รวบรวมผลผลิต จนถึงผู้ส่งออก ในฤดูร้อน ฤดูฝน และฤดูหนาว โดย สำรวจการปนเปื้อนในอุปกรณ์ที่ใช้สัมผัสหน่อไม้ฝรั่งในแปลง พบว่าหมวกพลาสติกปนเปื้อนมากที่สุดโดยพบ Coliform ประมาณ 6 \log_{10} cfu และพบ E. coil ในช่วง 5.2-6 \log_{10} cfu และรองลงมาคือตะกร้าโคยพบ Coliform ประมาณ 5.9 \log_{10} cfu และพบ $E.\ coil$ ในช่วง 0.4-5.1 \log_{10} cfu ขณะที่น้ำที่ใช้ล้างหน่อไม้ฝรั่งพบ Coliform เพียง 0.8-4.4 $\log_{10} \mathrm{cfu}/100 \mathrm{\ ml}$ และแทบจะไม่พบ $E.\ coil$ ทั้งนี้พบการปนเปื้อนมากที่สุดในฤดูหนาว การตรวจหน่อไม้ฝรั่งที่ผ่านการ ล้างน้ำและไม่ผ่านการล้างน้ำที่แปลงเกษตรกรพบการปนเปื้อนไม่แตกต่างกัน โดยพบ Coliform 4.2-4.9 log₁₀cfu/g และ E. coil ผันแปรมากตั้งแต่ 0-4.9 $\log_{10} \mathrm{cfu/g}$ และมีการปนเปื้อนในฤดูร้อนมากที่สุด ขณะที่ฤดูหนาวพบน้อยที่สุด การศึกษา ณ โรงคัดคุณภาพที่จุดผู้รวบรวมผลผลิต พบว่าการนำหน่อ ไม้ฝรั่งมาล้างน้ำคลอรีน 100 µl 1⁻¹ บริเวณโคน หน่อไม้ฝรั่งนาน 5 นาที ลด Coliform ได้ 0.6-1.8 log_{no}cfu/g ในฤดูฝนและหนาว แต่ในฤดูร้อนกลับทำให้มีการ ปนเปื้อนมากขึ้น สำหรับ E. coil ลดได้ประมาณ $0.3 \log_{10} \mathrm{cfu/g}$ แต่ในฤดูหนาวไม่พบการปนเปื้อนของ E. การศึกษาประสิทธิภาพของการล้าง ณ โรงคัดบรรจุผู้ส่งออก พบว่าการล้างด้วยน้ำคลอรีน 200 μ l 1 $^{-1}$ นาน 10 นาที ลด Coliform ได้ 0.2- $0.9 \log_{10} \mathrm{cfu/g}$ แต่ในฤดูฝนไม่พบ E. coil ปนเปื้อนทั้งก่อนล้างและหลังล้างน้ำคลอรีน ส่วนในฤดู หนาวและฤดูร้อนการล้างหน่อไม้ฝรั่งด้วยน้ำคลอรีนอาจทำให้มีการปนเปื้อนมากขึ้น ผลการทดลองทั้งหมดแสดงให้ เห็นว่าการปนเปื้อน Coliform และ E. coil ในกระบวนการผลิตหน่อ ไม้ฝรั่งเพื่อการส่งออกอยู่ในระดับที่ยอมรับ ได้ แต่ การลดการปนเปื้อนให้ต่ำลงยังทำได้ไม่สม่ำเสมอ และควรมีการควบคมการทำความสะอาดตั้งแต่ระดับแปลงโดยต้อง นำระบบ GAP มาประยกต์ใช้ในแปลงและนำหลักการ HACCP มาประยกต์ใช้ในกระบวนการหลังการเก็บเกี่ยว

^{*} วิทยาศาสตรมหาบัณฑิต (เทคโนโลยีหลังการเก็บเกี่ยว) มหาวิทยาลัยเกษตรศาสตร์. 92 หน้า.

Panida Phakkhawan*

Abstract

The contaminations of Escherichia coli (E. coil) and Coliform bacteria in asparagus destined for export were studied during crop processing, specifically at the farm production level, supplier's packaging warehouse and exporter's factory. The study was carried out during the rainy, dry and hot season. At the farm level, contamination of utensils and cleaning water was analyzed, particularly in 1) the plastic cap used for shoot tip coverage; 2) the basket for collecting asparagus; and 3) the cleaning water. The result showed that the highest contamination of Coliform and E. coil was found in the plastic cap used for shoot tip coverage, at about 6 log₁₀cfu and 5.2 - 6 log₁₀cfu, respectively. The second highest contamination of Coliform and E. coil was found in the collecting basket at about 5.9 log₁₀cfu and 0.4 - 5.1 log₁₀cfu, respectively. The lowest contamination of Coliform and E. coli was found in the cleaning water at a range of 0.8 - 4.4 log₁₀cfu/100 ml and 0.11 log₁₀cfu/100 ml., respectively. It is noteworthy that E. coil contamination was found to be highest during the dry season. Washing asparagus with tap water did not result in lower contamination. Coliform and E. coli were found at a range of 4.2-4.9 log₁₀cfu/g and 0-4.9 log₁₀cfu/g, respectively. Further study at the supplier's packaging warehouse showed that a washing treatment with a chlorine solution at 100 µll⁻¹ for 5 minutes was able to reduce Coliform and E. coil contaminations at a range of 0.6-1.8 and 0.3 log₁₀cfu/g, respectively. E. coil was not found during the dry season. However, results from the study during the hot season showed that a washing treatment with a chlorine solution increased the contamination of Coliform. At the exporter factory, washing with a 200 µll chlorine solution for 10 minutes decreased Coliform contamination a range of 0.2 - 0.9 log₁₀cfu/g. However, during the dry and hot seasons washing could increase contamination. The results of all experiments showed that contamination of Coliform and E. Coil were at acceptable levels. However, the procedure to reduce contamination was not very effective. The GAP and HACCP should be adopted during the production and postharvest processes, respectively.

_

^{*} Master of Science (Postharvest Technology), Kasetsart University. 92 p.